



AMERICAN COATINGS CORPORATION

Serving the Environmental Control Industry Since 1979

3037 NW 60th Street
Ft. Lauderdale, FL 33309

Toll-Free (800) 533-0151
Fax (954) 970-3690

ACC-555

Low Odor Mastic Remover
Organic Industrial Cleaner & Degreaser

ACC-555 has been developed as the "next generation" of organic, low odor mastic removers. It is an effective and economical stripper of asphalt cutback adhesives.

ACC-555 contains a unique high purity solvent base with very low levels of aromatics. The end result is a clear cleaning composition with a mild odor and higher solvent strength than competitive low odor products.

ACC-555's formulation contains more solvent content, yielding faster and more thorough removal than other low odor products.



Flash Point Higher than 142° F



K-B Value 30-35



High Purity Solvent Base



Virtually Nitrogen & Sulfur Free



More Solvent Per Gallon Than Other Low Odor Products

CLASS	Cleaning Compound
COLOR	Clear
SHIPPING CLASS	55
WEIGHT PER GALLON	6.80
FLASH POINT	>142° F
BOILING RANGE	350° F - 475° F
NITROGEN, ppm	<5
SULFUR, ppm	<5

APPLICATION SUGGESTIONS

Consult Material Safety Data before handling ACC-555. Keep MSDS available during usage. Sample applications are recommended to determine the product's desirability and most effective coverage rate. Use with sufficient mechanical ventilation.

METHOD A

1. Using easy-to-pour spout, soak the material to be removed. Allow enough time for ACC-555 to penetrate and loosen the material.
2. With cleaning tools, such as scrubbers, brooms, brushes or scrapers, remove the treated material.
3. When necessary, repeat the above steps.
4. Wash and rinse thoroughly with detergent and water. Repeat when necessary. Allow to dry. Surface must be clean prior to reinstallation.
5. Collect and dispose of all materials in accordance with all Federal, State and Local regulations.

METHOD B

1. Apply sufficient amount of ACC-555 to the material to be removed.
2. Begin cleaning operations quickly. Using scrubbers, brooms, scrapers or brushes, work ACC-555 into the treated material. Continue as required.
3. Repeat steps 3 through 5 of Method A.

American Coatings Corporation's (ACC) liability regarding this product is limited to the replacement of any materials which are found to be defective by ACC's laboratory. The user shall be solely responsible for determining the suitability of this product for each project onto which it is intended to be used. ACC makes no warranty, express or implied, with regard to this product.